

# DH-SD8C260PA-HNF

2M 60x Starlight IR WizMind Network PTZ Camera



WizMind

- 1/1.8" 2Megapixel STARVIS™ CMOS
- 60x optical zoom
- Starlight technology
- Max. 25/30 fps@2M
- IR distance up to 250 m
- H.265 encoding
- Two-way audio
- IR and white light, three night view modes
- IP67
- Auto-tracking
- Perimeter protection
- Face recognition

## System Overview

AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, and traffic data statistics. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and more devices. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.

## Functions

### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

### Starlight Technology

For challenging low-light conditions, Dahua's Starlight Ultra-low Light Technology offers the best in light sensitivity, capturing color in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

### PFA Technology

PFA technology has introduced new methods of judgment that ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms that ensure image clarity when zooming and that shorten focus time. This makes the camera highly advanced in its functions, substantially improving the quality of your experience.



### Environment (−40 °C to +70 °C, IP67)

Developed to operate in extreme conditions, Dahua camera can function in temperatures ranging from −40 °C to +70 °C (−40 °F to +158 °F) at 95% humidity. It was subjected to rigorous dust and water immersion tests, gaining its IP67 Ingress Protection certification, making it suitable for demanding outdoor applications.

### Auto-tracking

This feature controls the pan, tilt and zoom actions of the camera to automatically track an object in motion, to keep it in view of the camera. Tracking can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

### Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, a flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality videos without straining the network. Smart H.265+ technology outranks standard H.265 video compression, reducing bit rate and storage requirements by up to 70%.

### Scene

The Dahua PTZ AI network camera adopts advanced CNN deep learning algorithms to support Perimeter Protection. This highly accurate camera possesses a wide monitoring range and the PFA algorithm, allowing it to always present a clear, focused image while zooming. Leveraging the latest in starlight technology, the camera has strong low light performance, smooth controls, high-grade protection, and produces high quality images, meeting most of the requirements of video surveillance applications.

## Technical Specification

### Camera

Image Sensor	1/1.8" CMOS
Pixel	2 MP
Max. Resolution	1920 (H) × 1080 (V)
ROM	8 GB
RAM	2 GB
Electronic Shutter Speed	1/1 s–1/30,000 s
Scanning System	Progressive
Min. Illumination	Color: 0.005 lux@F1.4 B/W: 0.0005 lux@F1.4 0 lux (dual light fusion on)
Illumination Distance	80 m (262.46 ft) (dual light fusion-only white light on) 250 m (1,476.38 ft) (dual light fusion-only IR light on)
Illuminator On/Off Control	Zoom Prio; Manual; Smart IR; Off
Illuminator Number	10 (dual light fusion)
Wiper	Yes

### Lens

Focal Length	5.6 mm–336 mm			
Max. Aperture	F1.4–F4.5			
Field of View	H: 56.4°–1.2°; V: 32.7°–0.7°; D: 63.6°–1.7°			
Optical Zoom	60x			
Focus Control	Auto; semi-auto; manual			
Close Focus Distance	0.5 m–2 m (1.64–6.56 ft)			
DORI Distance	Detect	Observe	Recognize	Identify
	6,720 m (22,047.24 ft)	2,666.7 m (8,749.02 ft)	1,344 m (4,409.45 ft)	672 m (2,204.72 ft)

### PTZ

Pan/Tilt Range	Pan: 0° to 360° endless Tilt: –20° to +90°
Manual Control Speed	Pan: 0.1°/s–240°/s Tilt: 0.1°/s–100°/s
Preset Speed	Pan: 0.1°/s–200°/s; Tilt: 0.1°/s–60°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Power-off Memory	Yes
Idle Motion	Preset; Pattern; Tour; Scan
PTZ Protocol	DH-SD Pelco-P/D (auto recognition)

### Intelligence

Video Metadata	Support human body, human face, motor vehicle and non-motor vehicle image capture and attributes extraction.
----------------	--

IVS (Perimeter Protection)	Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, etc.
Face Recognition	Yes

### Video

Video Compression	H.265; H.264M; H.264H; MJPEG; Smart H.265; Smart H.264
Streaming Capability	3 streams
Resolution	1080p (1920 × 1080); 960p (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Video Frame Rate	Main stream: 1080p/960p/720p (1–25/30 fps) Sub stream 1: D1/VGA/CIF (1–25/30 fps) Sub stream 2: 1080p/960p/720p (1–25/30 fps)
Bit Rate Control	CBR; VBR
Video Bit Rate	H.264: 1792 kbps–9216 kbps H.265: 512 kbps–5632 kbps
Day/Night	Auto (ICR); Color; B/W
BLC	Yes
WDR	120 dB
HLC	Yes
White Balance	Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp
Gain Control	Auto; manual
Noise Reduction	2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Defog	Optical
Digital Zoom	16x
Image Rotation	180°
Privacy Masking	Up to 24 areas can be set, with up to 8 areas in the same view
S/N Ratio	≥55 dB

### Audio

Audio Compression	G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; PCM
-------------------	---

### Network

Network Port	RJ-45 (10/100 Base-T)
Network Protocol	HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; QoS; FTP; UPnP; ICMP; SNMP; IGMP; RTP; PPPoE; RTMP; TCP
Interoperability	ONVIF (Profile S&G&T); GB/T28181; CGI
Streaming Method	Unicast; Multicast
User/Host	20 (total bandwidth: 64 M)
Storage	FTP; Micro SD card (512 GB); NAS
Browser	IE 7 and later versions Chrome 45 and later versions Firefox 52ESR and earlier versions Safari
Management Software	Smart PSS; DSS; IVSS

Mobile Client	iOS; Android
Port	
Analog Output	1 channel (CVBS output, BNC)
RS-485	1 (baud rate: 1200 bps–115200 bps)
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)
Two-way Audio	Yes
Alarm Input	7 (on-off value input: 0–5 VDC)
Alarm Output	2
Alarm Linkage	Capture; preset; tour; pattern; recordings on SD card; alarm digital input; client E-map; send email
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; decoder state detection; memory card state detection; memory space detection; power exception detection

Power	
Power Supply	36 VDC, 2.23 A (± 25%)
Power Consumption	Basic: 18 W Max.: 33 W (illuminator + PTZ)

Environment	
Operating Temperature	–40 °C to +70 °C (–40 °F to 158 °F)
Operating Humidity	≤95%
Protection	IP67; TVS 8000 V lightning proof; surge protection; voltage transient protection

Structure	
Product Dimensions	442 mm × Φ262 mm (17.40" × Φ10.31")
Net Weight	10.3 kg (22.71 lb)
Gross Weight	12.5 kg (27.56 lb)

### Ordering Information

Type	Model	Description
2 MP Camera	DH-SD8C260PA-HNF	2M 60x Starlight IR WizMind Network PTZ Camera
	DH-SD8C260PA-HNF	2M 60x Starlight IR WizMind Network PTZ Camera
Accessories	DC36V/2.23A	Power Adapter
	PFB306W-S	Wall Mount Bracket
	PFB300C-S	Ceiling Mount Bracket
	PFA150 + PFB306W-S	Vertical Pole Mount Bracket
	PFA150 + PFB300C-S	Horizontal Pole Mount Bracket

### Accessories

Included:



DC36V/2.23A Power Adapter



PFB306W-S Wall Mount Bracket

Optional:



PFB300C-S Ceiling Mount Bracket



PFA150 + PFB306W-S Vertical Pole Mount Bracket



PFA150 + PFB300C-S Horizontal Pole Mount Bracket

Wall Mount PFB306W-S	Ceiling Mount PFB300C-S	Pole Mount(Vertical) PFA150+PFB306W-S
Pole Mount(Horizontal) PFA150+PFB300C-S		

### Dimensions (mm[inch])

